

EndurAir™

Rotary Screw Air Compressors



5–20 HP
ELA 5/7.5/10, ELB 15, ELC 20
Load/No Load Control



Compact

The EndurAir Series is more reliable, economical and compact—perfect for point-of-use placement in even the most rugged conditions.

Durable

With tens of thousands of Enduro airends in operation worldwide, we're not just talking about durability, we've proven it. The air end has been in the marketplace for years with failure rates well below world class standards.

Performance Driven

This load/no-load compressor is managed by a new microprocessor controller. It monitors and regulates the number of starts per hour and controls the unloaded periods. In short cycling situations, the starts are delayed—minimizing energy consumption and optimizing performance of the compressor.

Efficient

A newly designed inlet valve for this “tried and true” compressor optimizes electrical consumption whether the compressor is fully loaded or unloaded.

Service Friendly

The design of the EndurAir makes general maintenance a snap and ensures minimal downtime. One-piece removable side and rear panels provide easy access to critical service points—including the drive belts, pulleys and the spin on oil filter and oil separator.

Proven Results

Gardner Denver product development is a balance of technology, efficiency and performance—all focused on meeting your demand for compressed air.

GD
GARDNER DENVER

Experience Proven Results

Technical Data

EndurAir 5–20 HP, 60 Hz



Gardner Denver Model	Rated Pressure	Capacity at Rated Pressure	Motor power	Net weight	Dimensions L x W x H	Noise level
	psig	acfm	hp	lbs	inches	dBA
ELA 5	100	21	5	315	26 x 27 x 34	69
	125	19				
	150	18				
	175	15				
ELA 7.5	100	29	7.5	322	26 x 27 x 34	70
	125	26				
	150	23				
	175	20				
ELA10	100	40	10	330	26 x 27 x 34	71
	125	36				
	150	32				
	175	29				
ELB 15	100	57	15	411	28 x 30 x 41	74
	125	54				
	150	49				
	175	43				
ELC 20	100	84	20	463	28 x 30 x 41	74
	125	75				
	150	66				
	175	62				

Standard Equipment

- Advanced Air End design guarantees a longer life and greater endurance that results in lower power consumption.
- Transmission between the motor and the Air End is provided through long life first class belts.
- Thermal mixing valve optimizes the oil cycling temperature and prevents condensation inside the oil separator and hoses.
- An external oil separator cartridge (less than 3 ppm) is provided to simplify maintenance.
- Electrical Control Panel with Full Voltage Starting for 5 through 20 HP. Regulation CEI EN 60204-1 with main switch.
- TEFC Electric Motor has an IP55 Class F, tropical insulation classification.
- All Internal Flex Hoses are rated for temperatures of 300° F.

- The Combination Oil Cooler/Aftercooler is adequately sized to provide an air temperature out of the compressor of not greater than 18–20° F of the ambient temperature.
- Low dBA Acoustical Enclosures
- V-Belt Drive with a Totally Enclosed Belt Guard
- Inlet Filter
- Oil Filter with Bypass
- Air/Oil Separator
- Vertical Draft Air/Oil Cooler
- Minimum Pressure Check Valve
- Oil Level Sight Gauge
- Dual High Temperature Shutdown Sensors
- Hour Meters for Run Time and Loaded Time
- Factory Fill of AEON® 4000
- AirPlus Microprocessor Control System
- 24 Volt Control Circuit Protection

- Full Voltage Starting on 10–20 HP
- TEFC Motors
- Start Delay Blow Down timer
- Emergency Shutdown Switch
- Phase Reversal Protection
- Motor Overload Protection
- Easy Adjusting Belt Tensioner
- Electrical Controller is UL/cUL Listed
- Electric Disconnect Safety Switch to the Motor

Optional Equipment

- 80 Gallon Horizontal Receiver (5, 7.5, 10 HP)
- 120 Gallon Horizontal Receiver (15 & 20 HP)
- Auto Tank Drain

Gardner Denver®

www.GardnerDenverProducts.com maggie@gardnerdenver.com

Gardner Denver, Inc. 1800 Gardner Expressway, Quincy, IL 62305
Customer Service Department Telephone: (800) 682-9868 FAX: (217) 224-7814



Member



Please recycle after use.